

LED indoor light sensor

RS 200. Premiere!

Indoor light with Bluetooth Connect connectivity.

The RS 200 is the first Connect LED indoor light in our indoor range for ceilings and walls. This means that it can be easily adjusted, networked and operated via Bluetooth. No cable. No stress. The light comes in a high-quality, anthracite-coloured aluminium enclosure and boasts an intelligent soft light start alongside the 360° high-frequency sensor. In this way, you automatically create an all-round beautiful room atmosphere, which is rounded off by an ambient light on the wall.



Mesh
Connect

New Bluetooth Mesh
Connect Standard



Start-up, setting and networking
via the free STEINEL Connect app














All STEINEL Bluetooth products
can be networked with one another
and grouped together

LED indoor light sensor

RS 200



 <p>Set-up and connection via the STEINEL Connect app</p>	 <p>High-frequency 360° sensor</p>	 <p>max. 8 m</p>	 <p>2–2000 lx</p>	 <p>5 s–60 min</p>
 <p>Incl. STEINEL LED system</p>	 <p>Ambient lighting</p>	 <p>High-quality aluminium enclosure</p>	<p>Technical specifications</p> <p>Dimensions (L x W x H) Ø 263 x 53 mm</p> <p>Mounting..... Wall, ceiling</p> <p>Max. mounting height 4.00 m</p> <p>Output 17.1 W</p> <p>Light flux 1165 lm</p> <p>Efficiency 68 lm/W</p> <p>Colour temperature 3000 K / SDCM3</p> <p>LED life expectancy (max. °C) 36,000 hours</p> <p>Soft light start..... Included</p> <p>Networking Via Bluetooth</p> <p>IP rating IP54</p> <p>Ambient temperature -20 – +40 °C</p> <p>Enclosure material Aluminium</p> <p>Order details</p> <p>RS 200 SC 4007841 078782</p> <p>RS 200 C (without sensor) 4007841 078775</p>	
 <p>Wireless networking</p>	 <p>Intelligent soft light start</p>	 <p>263 263 53</p> 