Motion detector - Professional Line



COM1 - black EAN 4007841 066215 Article number 066215







Function description

Makes all the difference outside. Precisely where you want it to. iHF 3D motion detector, ideal for facades, carports, parking areas and patios. 160° iHFsensor with 5 m reach, 3D aerial technology, identifies and distinguishes between moving objects, no inadvertent triggering any more by small animals, very low or high temperatures. Detects everything equally well whichever direction it is approached from. Easy to adjust and interconnect by app and Bluetooth.

Technical specifications

Dimensions (L x W x H)	120 x 117 x 120 mm	Mounting height max.	
With motion detector	Yes	Optimum mounting height	
Manufacturer's Warranty	5 years	HF-system	
Settings via	Potentiometers, Bluetooth	Detection angle	
With remote control	No	Angle of aperture	
Version	COM1 - black	Sneak-by guard	
PU1, EAN	4007841066215	Capability of masking out inc	
Туре	Motion detectors	segments	
Application, place	Outdoors	Electronic scalability	
Application, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway	Mechanical scalability	
		Reach, radial	
		Reach, tangential	
Colour	black	Transmitter power	
Colour, RAL	9005	Functions	
Includes corner wall mount	No		
Installation site	wall	Twilight setting	
Installation	Surface wiring, Wall	Time setting	

Mounting height max.	2,00 m
Optimum mounting height	1,8 m
HF-system	5,8 GHz
Detection angle	160 °
Angle of aperture	100 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	r = 5 m (35 m ²)
Reach, tangential	r = 5 m (35 m ²)
Transmitter power	< 1 mW
Functions	Normal / test mode, Manual ON / ON-OFF
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.

https://www.steinel.de

Subject to technical modifications

10.2023 Page 1 from 3

Motion detector - Professional Line

iHF 3D

COM1 - black EAN 4007841 066215 Article number 066215

. steinel

Technical specifications

IP-rating	IP54
Ambient temperature	-20 - 50 °C
Material	Plastic
Mains power supply	220 – 240 V / 50 – 60 Hz
Switching output 1, resistive	2000 W
Technology, sensors	iHF (intelligent high-frequency technology), Light sensor
Mounting height	1,80 – 2,00 m

Basic light level function	No
Main light adjustable	No
Twilight setting TEACH	Yes
Constant-lighting control	No
Interconnection	Yes
Type of interconnection	Master/master
Interconnection via	Cable, Bluetooth

Motion detector - Professional Line

iHF 3D

COM1 - black EAN 4007841 066215 Article number 066215



Detection Zone



Dimension Drawing



Possible mounting height: 1,80 m – 2,00 m Orange: radial and tangential 3 scalable axes

Master circuit diagram

